




PLUS 2P SX

WORKING CONDITIONS

Max working pressure _____ 8 bar (116 psi)
 Max working temperature _____ 45°C (113°F)
 Min working temperature _____ 4°C (39,2°F)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head: reinforced polypropylene.
 Bowl: SAN.
 O-ring: EPDM.
 Breather-valve: body polypropylene, o-ring EPDM.
 IN/OUT brass threads: CW 614 N brass.



PLUS 2P SX clear housings

HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA117P111	CADET PLUS 2P MFO SX AS	4"	1/2"	BRASS-BSP	169	133	130
RA117P411	CADET PLUS 2P AFO SX AS	4"	3/4"	BRASS-BSP	169	133	130
RA117P711	CADET PLUS 2P BFO SX AS	4"	1"	BRASS-BSP	173	145	130
RA119P111	JUNIOR PLUS 2P MFO SX AS	7"	1/2"	BRASS-BSP	241	133	130
RA119P411	JUNIOR PLUS 2P AFO SX AS	7"	3/4"	BRASS-BSP	241	133	130
RA119P711	JUNIOR PLUS 2P BFO SX AS	7"	1"	BRASS-BSP	247	145	130
RA121P111	SENIOR PLUS 2P MFO SX AS	10"	1/2"	BRASS-BSP	315	133	130
RA121P411	SENIOR PLUS 2P AFO SX AS	10"	3/4"	BRASS-BSP	315	133	130
RA121P711	SENIOR PLUS 2P BFO SX AS	10"	1"	BRASS-BSP	321	145	130

HOUSINGS WITH PLASTIC BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA117P211	CADET PLUS 2P MFP SX AS	4"	1/2"	PLASTIC-BSP	169	133	130
RA117P511	CADET PLUS 2P AFP SX AS	4"	3/4"	PLASTIC-BSP	169	133	130
RA117P811	CADET PLUS 2P BFP SX AS	4"	1"	PLASTIC-BSP	173	145	130
RA119P211	JUNIOR PLUS 2P MFP SX AS	7"	1/2"	PLASTIC-BSP	241	133	130
RA119P511	JUNIOR PLUS 2P AFP SX AS	7"	3/4"	PLASTIC-BSP	241	133	130
RA119P811	JUNIOR PLUS 2P BFP SX AS	7"	1"	PLASTIC-BSP	247	145	130
RA121P211	SENIOR PLUS 2P MFP SX AS	10"	1/2"	PLASTIC-BSP	315	133	130
RA121P511	SENIOR PLUS 2P AFP SX AS	10"	3/4"	PLASTIC-BSP	315	133	130
RA121P811	SENIOR PLUS 2P BFP SX AS	10"	1"	PLASTIC-BSP	321	145	130

HOUSINGS WITH PLASTIC NPT THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA117P516	CADET PLUS 2P AFP NPT SX AS	4"	3/4"	PLASTIC-NPT	169	133	130
RA117P816	CADET PLUS 2P BFP NPT SX AS	4"	1"	PLASTIC-NPT	173	145	130
RA119P516	JUNIOR PLUS 2P AFP NPT SX AS	7"	3/4"	PLASTIC-NPT	241	133	130
RA119P816	JUNIOR PLUS 2P BFP NPT SX AS	7"	1"	PLASTIC-NPT	247	145	130
RA121P516	SENIOR PLUS 2P AFP NPT SX AS	10"	3/4"	PLASTIC-NPT	315	133	130
RA121P816	SENIOR PLUS 2P BFP NPT SX AS	10"	1"	PLASTIC-NPT	321	145	130

HOUSINGS WITH PLASTIC BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA117P214	CADET PLUS 2P MMP SX AS	4"	1/2"	PLASTIC-BSP	169	175	130
RA117P514	CADET PLUS 2P AMP SX AS	4"	3/4"	PLASTIC-BSP	169	175	130
RA117P814	CADET PLUS 2P BMP SX AS	4"	1"	PLASTIC-BSP	173	175	130
RA119P214	JUNIOR PLUS 2P MMP SX AS	7"	1/2"	PLASTIC-BSP	241	175	130
RA119P514	JUNIOR PLUS 2P AMP SX AS	7"	3/4"	PLASTIC-BSP	241	175	130
RA119P814	JUNIOR PLUS 2P BMP SX AS	7"	1"	PLASTIC-BSP	247	175	130
RA121P214	SENIOR PLUS 2P MMP SX AS	10"	1/2"	PLASTIC-BSP	315	175	130
RA121P514	SENIOR PLUS 2P AMP SX AS	10"	3/4"	PLASTIC-BSP	315	175	130
RA121P814	SENIOR PLUS 2P BMP SX AS	10"	1"	PLASTIC-BSP	321	175	130