

Technical Data Sheet

General data	
Frame size	160
Housing material	Casting iron
Install model	B5
Type of feet	Removable feet (Standard) <i>Fixed feet</i> (Optional)
Net weight	112 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) <i>Customizable</i> (Optional)
Rotation direction	Clockwise (Standard) <i>Counter clockwise</i> (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M32× 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) <i>Customizable</i> (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	7.5	kW
Frequency	50	Hz
Voltage (±5%)	400 690 480 828	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	960 1152	RPM @ 50Hz RPM @ 60Hz
Rated current	16.2 9.35	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	7.5	×In
Rated torque	74.61	Nm (Mn)
Starting torque	2.3	×Mn
Breakdown torque	2.8	×Mn
Efficiency	89.1 90.3 88	IE3 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.75	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) <i>Customizable</i> (Optional)	
Bearings type	6309 C3 (DE) 6309 C3 (NDE)	
Lifetime of bearings		- hours
Allowed radial load		2028 N
Allowed axial load		21200 N
Grease type	polyurea-based grease	
Lubrication interval of NDE bearing	22500 h	
Lubrication interval of DE bearing	22500 h	
Moment of inertia	0.087260	Kg*m ²
Noise level	73	dB(A)

No. 303 Kangliu Road Kangqiao Town Pudong Shanghai, 201315, China

Tel: +86 (21) 6819 2006, Fax: +86 (21) 5812 9366, Email: info@techtom.net.cn, Website: www.techtom.com